



PREMIUM WHITE ELASTOMERIC FINISH COAT

UNIFLEX BASE COAT

6" POLYESTER FABRIC FULLY EMBEDDED

UNIFLEX ACRYLIC PATCHING CEMENT

METAL ROOF PANELS

FASTENER

1"  
2" SEAM TAPE  
CENTERED OVER  
SEAM

TYPICAL VERTICAL SEAM

2" SEAM TAPE

SEAM TAPE OPTION

- IN LIEU OF POLYESTER REINFORCEMENT, INSTALL 4" OR 6" (AS NEEDED) SEAM TAPE CENTERED OVER SEAM COMPLETELY COATED WITH UNIFLEX PREMIUM ELASTOMERIC

NOTES:

1. SURFACE MUST BE CLEAN, DRY AND IN SOUND CONDITION. REMOVE ALL OIL, GREASE, DUST, DIRT, LOOSE RUST AND OTHER FOREIGN MATERIAL TO ENSURE ADEQUATE ADHESION.
2. APPLY UNIFLEX RUST INHIBITIVE METAL PRIMER PRIOR TO REPAIRS AND COATING IF METAL SURFACE OXIDATION IS PRESENT
3. REFER TO APPROPRIATE UNIFLEX PREMIUM ELASTOMERIC SPECIFICATION.



UNIFLEX PREMIUM ELASTOMERIC SYSTEM

PANEL SEAM DETAIL

DATE: 3/25/11

SHEET NO:

NOT TO SCALE

MT-S-1