


EXISTING PLUMBING VENT

STORM COLLAR (AS NEEDED)

METAL ROOF PANEL

6" MIN.



PLAN VIEW

SPLICED POLYESTER FABRIC PIPE WRAP

POLYESTER FABRIC PIPE COVER (REINFORCED)

PREMIUM WHITE ELASTOMERIC FINISH COAT

UNIFLEX BASE COAT

POLYESTER FABRIC PIPE COVER (REINFORCED)

SPLICED POLYESTER FABRIC PIPE WRAP

UNIFLEX PREMIUM ELASTOMERIC

NOTES:

1. SURFACE MUST BE CLEAN, DRY AND IN SOUND CONDITION. REMOVE ALL OIL, GREASE, DUST, DIRT, LOOSE RUST AND OTHER FOREIGN MATERIAL TO ENSURE ADEQUATE ADHESION.
2. APPLY UNIFLEX RUST INHIBITIVE METAL PRIMER PRIOR TO REPAIRS AND COATING IF METAL SURFACE OXIDATION IS PRESENT
3. REFER TO APPROPRIATE UNIFLEX PREMIUM ELASTOMERIC SPECIFICATION.



UNIFLEX PREMIUM ELASTOMERIC SYSTEM

PIPE PENETRATION DETAIL

DATE: 3/25/11

SHEET NO:

MT-P-1

NOT TO SCALE