

A P

P

L

Y

Uniflex Acrylic Snapshot



Existing Spray Polyurethane Foam (SPF)

P Conduct: Moisture Survey & Adhesion Tests

R Repair: Damaged SPF

Replace: Wet Areas, Pitch Pan Sealants, Termination Sealants

P Clean: Pressure Wash

A Detail: 2.8 # SPF

R Apply: Uniflex Premium 41-320 Gray Base coat
E Apply: Uniflex Premium 41-300 Finish coat

SPF: Repair any damaged existing SPF with new SPF material

Basecoat: Apply Uniflex Premium Acrylic Gray Basecoat at 1.0 gallons per square. (16 wet mils)

Finishcoat Apply Uniflex Premium 41-300 at 1.0 gallons per square. (16 wet mils)

W A R R	5-15 Years	UNIGUARD ™ Materials Warranty	Ten Year Available No Cost or Pre-Approval Required	
A N	Mn-15	UNIGUARD [™] Systems Warranty	Pre-Approval Required- Warranty Fee Required	
T Y	Years		Ten Year Available	

	Uniflex Website	P R	Uniflex 41-300 Premium White Finish Coat
L I	Uniflex Warranty	O D	Uniflex 41-320 Gray Acrylic Basecoat
N K	Full Specification	U	2.8 # Spray Polyurethane Foam
S	Roof Calculator	T	
		S	



Need a Moisture Survey?

Ask Your Uniflex Regional Manager about Uniflex Roof View Thermal Imaging