



Uniflex Silicone Snapshot

Existing Spray Polyurethane Foam (SPF)



**P
R
E
P
A
R
E**

Conduct: *Moisture Survey & Adhesion Tests*
Repair: *Damaged SPF*
Replace: *Wet Areas, Pitch Pan Sealants, Termination Sealants*
Clean: *Pressure Wash*
Detail: *2.8 # SPF*
Apply: *Uniflex Silicone 44 Finish-coat*

**A
P
P
L
Y**

SPF: *Repair any damaged existing SPF with new SPF material*

Basecoat: *Not Required*

Finishcoat *10 Year System: Apply Uniflex Silicone 44 at 1.5 gallons per square. (24 wet mils)*

**W
A
R
R
A
N
T
Y**

	UNIGUARD™ Materials Warranty
	UNIGUARD™ Systems Warranty

Ten Year Available

No Cost or Pre-Approval Required

Pre-Approval Required- Warranty Fee Required

Ten Year Available

**L
I
N
K
S**

Uniflex Website
Uniflex Warranty
Full Specification
Roof Calculator

**P
R
O
D
U
C
T
S**

Uniflex Silicone 44 White Finish Coat

Spray Polyurethane Foam



Need a Moisture Survey?

Ask Your Uniflex Regional Manager about Uniflex Roof View Thermal Imaging

NOTE: This Snapshot is not designed to replace the full system specification. Full specifications are available at www.uniflexroof.com/specifications. Contractor must be a Uniflex Approved Applicator for System Warranties.