


# Uniflex Silicone Snapshot

Structural Metal 10/15



<b>P R E P A R E</b>	<b>Conduct:</b>	<b>Adhesion Tests</b>
	<b>Repair:</b>	<b>Open Laps, Flashings, Damaged Metal, Fasteners</b>
	<b>Replace:</b>	<b>Damaged Metal, Pitch Pan Sealants, Termination Sealants</b>
	<b>Clean:</b>	<b>Pressure Wash</b>
	<b>Apply:</b>	<b>Prime Rust</b>
	<b>Detail:</b>	<b>Uniflex One Flash</b>
	<b>Apply:</b>	<b>Uniflex Silicone 44 Finish-coat</b>

<b>A P P L Y</b>	<b>OneFlash:</b>	<i>Detail all flashings and penetrations. Apply OneFlash at 60 wet mils, extending 2 inches on each side of the overlap seams.</i>
	<b>Basecoat:</b>	<i>Apply Uniflex Silicone 44 at 1.0 gallons per square (16 wet mils) over metal panel laps</i>
	<b>Finishcoat</b>	<i>10 Year System: Apply Uniflex Silicone 44 at 1.5 gallons per square. (24 wet mils) 15 Year System: Apply Uniflex Silicone 44 at 2.0 gallons per square (32 wet mils)</i>

<b>W A R R A N T Y</b>		<b>UNIGUARD™</b> Materials Warranty	<b>Ten or Fifteen Year Available</b>
		<b>UNIGUARD™</b> Systems Warranty	<b>No Cost or Pre-Approval Required</b>
			<b>Pre-Approval Required- Warranty Fee Required</b>
			<b>Ten or Fifteen Year Available</b>

<b>L I N K S</b>	<b>Uniflex Website</b>	<b>P R O D U C T S</b>	<b>Uniflex Silicone 44 White Finish Coat</b>
	<b>Uniflex Warranty</b>		<b>Uniflex One Flash</b>
	<b>Full Specification</b>		<b>Uniflex Rust Inhibitive Primer</b>
	<b>Roof Calculator</b>		



**UNIFLEX**  
Fluid Applied Roofing Systems  
**ROOFVIEW**

**Need a Moisture Survey?**

**Ask Your Uniflex Regional Manager about Uniflex Roof View Thermal Imaging**

NOTE: This Snapshot is not designed to replace the full system specification. Full specifications are available at [www.uniflexroof.com/specifications](http://www.uniflexroof.com/specifications). Contractor must be a Uniflex Approved Applicator for System Warranties.