



Uniflex Silicone Snapshot

Structural Metal 20



P R E P A R E	Conduct:	Adhesion Tests
	Repair:	Open Laps, Flashings, Damaged Metal, Fasteners
	Replace:	Damaged Metal, Pitch Pan Sealants, Termination Sealants
	Clean:	Pressure Wash
	Apply:	Prime Rust
	Detail:	Uniflex One Flash
	Apply:	Uniflex Silicone 44 Finish-coat

A P P L Y	OneFlash:	<i>Detail all flashings and penetrations. Apply OneFlash at 60 wet mils, extending 2 inches on each side of the overlap seams and extending 1 inch of each side of end and side laps.</i>
	Basecoat:	<i>Not Required</i>
	Finishcoat	<i>20 Year System: Apply Uniflex Silicone 44 at 2.5 gallons per square (40 wet mils)</i>

W A R R A N T Y		UNIGUARD™ Materials Warranty	Ten or Fifteen Year Available
		UNIGUARD™ Systems Warranty	No Cost or Pre-Approval Required
			Pre-Approval Required- Warranty Fee Required
			Twenty Year Available

L I N K S	Uniflex Website	P R O D U C T S	Uniflex Silicone 44 White Finish Coat
	Uniflex Warranty		Uniflex One Flash
	Full Specification		Uniflex Rust Inhibitive Primer
	Roof Calculator		



UNIFLEX®
Fluid Applied Roofing Systems
ROOFVIEW

Need a Moisture Survey?

Ask Your Uniflex Regional Manager about Uniflex Roof View Thermal Imaging

NOTE: This Snapshot is not designed to replace the full system specification. Full specifications are available at www.uniflexroof.com/specifications. Contractor must be a Uniflex Approved Applicator for System Warranties.