



Uniflex Acrylic Snapshot

Existing Spray Polyurethane Foam (SPF)



P R E P A R E	Conduct:	<i>Moisture Survey & Adhesion Tests</i>
	Repair:	<i>Damaged SPF</i>
	Replace:	<i>Wet Areas, Pitch Pan Sealants, Termination Sealants</i>
	Clean:	<i>Pressure Wash</i>
	Detail:	<i>2.8 # SPF</i>
	Apply:	<i>Uniflex Premium 41-320 Gray Base coat</i>
	Apply:	<i>Uniflex Premium 41-300 Finish coat</i>

A P P L Y	SPF:	<i>Repair any damaged existing SPF with new SPF material</i>
	Basecoat:	<i>Apply Uniflex Premium Acrylic Gray Basecoat at 1.0 gallons per square. (16 wet mils)</i>
	Finishcoat	<i>Apply Uniflex Premium 41-300 at 1.0 gallons per square. (16 wet mils)</i>

W A R R A N T Y		UNIGUARD™ Materials Warranty	Ten Year Available
	No Cost or Pre-Approval Required		
		UNIGUARD™ Systems Warranty	Pre-Approval Required- Warranty Fee Required
	Ten Year Available		

L I N K S	Uniflex Website	P R O D U C T S	Uniflex 41-300 Premium White Finish Coat
	Uniflex Warranty		Uniflex 41-320 Gray Acrylic Basecoat
	Full Specification		2.8 # Spray Polyurethane Foam
	Roof Calculator		



Need a Moisture Survey?

Ask Your Uniflex Regional Manager about Uniflex Roof View Thermal Imaging

NOTE: This Snapshot is not designed to replace the full system specification. Full specifications are available at www.uniflexroof.com/specifications. Contractor must be a Uniflex Approved Applicator for System Warranties.