



Uniflex Acrylic Snapshot

Structural Metal



P R E P A R E	Conduct:	Adhesion Tests
	Repair:	Open Laps, Flashings, Damaged Metal, Fasteners
	Replace:	Damaged Metal, Pitch Pan Sealants, Termination Sealants
	Clean:	Pressure Wash
	Prime	Prime Rust
	Detail:	Uniflex One Flash
	Apply:	Uniflex Premium Gray Base-coat 41-320 Uniflex Premium 41-300 Finish-coat

A P P L Y	OneFlash:	<i>Detail all flashings and penetrations. Apply OneFlash at 60 wet mils, extending 2 inches on each side of the overlap seams.</i>
	Basecoat:	<i>Apply Uniflex Acrylic Gray Basecoat at 1.5 gallons per square. (24 wet mils) over metal panel laps. Apply Uniflex Acrylic Gray Basecoat at 1.0 gallons per square. (16 wet mils) over field of roof.</i>
	Finishcoat	<i>10 Year System: Apply Uniflex Premium 41-300 at 1.5 gallons per square. (24 wet mils) 15 Year System: Apply Uniflex Premium 41-300 at 2.0 gallon per square (32wet mils)</i>

W A R R A N T Y		UNIGUARD™ Materials Warranty	Ten or Fifteen Year Available
		UNIGUARD™ Systems Warranty	Pre-Approval Required- Warranty Fee Required
			Ten or Fifteen Year Available

L I N K S	Uniflex Website	P R O D U C T S	Uniflex 41-300 Premium White Finish Coat
	Uniflex Warranty		Uniflex 41-320 Gray Acrylic Basecoat
	Full Specification		Uniflex One Flash
	Roof Calculator		Uniflex Rust Inhibitive Primer *

**See full specification for previously coated roofs.*



Need a Moisture Survey?

Ask Your Uniflex Regional Manager about Uniflex Roof View Thermal Imaging

NOTE: This Snapshot is not designed to replace the full system specification. Full specifications are available at www.uniflexroof.com/specifications. Contractor must be a Uniflex Approved Applicator for System Warranties.